



Product: OFR
Date: 03/2011

NOT FOR NAVIGATIONAL USE

HIGH-RESOLUTION GEOLOGIC MAPPING OF THE INNER CONTINENTAL SHELF: BOSTON HARBOR AND APPROACHES, MASSACHUSETTS

Sheet 1. Shaded-relief topography of seafloor (color).

Seth D. Ackerman, Bradford Butman, Walter A. Barnhardt, William W. Danforth and James M. Crocker

HIGH-RESOLUTION GEOLOGIC MAPPING OF THE INNER CONTINENTAL SHELF: BOSTON HARBOR AND APPROACHES, MASSACHUSETTS

U.S. Geological Survey Open File Report 2006-1008
Map Sheet 1: Shaded-relief topography of seafloor (color)

Introduction

A series of five map sheets show the sea floor topography and geology of Boston Harbor and Approaches. Sheet 1 is at a scale of 1:250,000. Sheet 2 is at a scale of 1:60,000. Sheet 3 shows sea floor topography and geology of the inner harbor. Sheet 4 shows sea floor topography and geology of the outer harbor. Sheet 5 shows sea floor topography and geology of the approaches. The maps show bathymetric contours, geologic contours, and geologic units. The maps are based on data collected from 1995 to 2005.

These maps are produced as part of a cooperative effort by the U.S. Geological Survey (USGS), the Massachusetts Office of Coastal Zone Management (CMZ), the Massachusetts Office of State Planning and Economic Development (MOSPED), the Massachusetts Office of Environmental Affairs (MOEA), and the Massachusetts Office of Statewide Enterprise Information Systems (SEIS). The maps are part of the USGS Open File Report (Ackerman and others, 2006) mapping data collection, processing, and analysis of geophysical and geologic data. The report on ODFR 2006-1008 also includes all of the data in GIS format and as part of an ESRI ArcView project.

Data and Methods

The bathymetric and sidescan-sonar data used to generate these maps were collected as part of hydrographic surveys of the navigable areas within Boston Harbor and its approaches carried out by NOAA in 2000 and 2001 (surveys H15090, H01991, H11092, and H01994) by the NOAA ship William G. Mearns. These cruises acquired sidescan-sonar data over an area of 150 km² and single-beam bathymetric data over an area of approximately 37% of the survey area. The multibeam echosounder data were collected in navigation channels and at approximately 400 m depth in the outer harbor. The sidescan-sonar data were collected in navigation channels and at approximately 400 m depth in the outer harbor. The sidescan-sonar data were collected in navigation channels and at approximately 400 m depth in the outer harbor. The sidescan-sonar data were collected in navigation channels and at approximately 400 m depth in the outer harbor.

The hydrographic surveys were designed for target identification and therefore NOAA collects overlapping sidescan-sonar data to ensure complete coverage of the sea floor. An EpiLog model 272-T (100 kHz) and a Simrad EK60 sidescan sonar were used for the sidescan surveys. Sidescan and vessel configurations were varied between and within individual surveys. The sidescan-sonar data were processed to correct for magnetic and geometric distortions inherent in sidescan data.

Map Sheets

The shaded-relief bathymetric maps (sheets 1 and 2) were created by vertically exaggerating the sea floor topography by a factor of 10 and artificially flattening the sea floor by a factor of 10. The bathymetric contours are shown at 1 m intervals. The shaded-relief maps are based on data collected from 1995 to 2005. The bathymetric contours are shown at 1 m intervals. The shaded-relief maps are based on data collected from 1995 to 2005. The bathymetric contours are shown at 1 m intervals. The shaded-relief maps are based on data collected from 1995 to 2005.

Some artifacts are present within the data. These include small high and low, and unusual-looking patterns oriented parallel or perpendicular to survey tracks. Artifacts may be due to environmental conditions on the day data collection and processing. Techniques were generally not parallel to the major channels in Boston Harbor and around the harbor islands. They were predominantly north-south in the harbor approaches. Slight misalignments in the geographic lines in the sidescan-sonar (sheet 2 and 4) are artifacts of data collection and processing. These occur where acquisition parameters in one swath are different from the adjacent swath, making it difficult to match the geographic lines along the entire length of the line. Areas that could not be interpreted because they were too shallow (typically less than a few meters deep) are shown in light gray.

Features

This study encompasses Boston Inner Harbor, Boston Outer Harbor, the northern approaches to Boston Harbor (Broad Sound north of the Harbor Islands to Nahant), and the southern approaches to Boston Harbor (Outer Harbor Islands and approaches east of Nahant Beach). The bathymetric and geologic data show the general distribution of surficial sediments. The approaches to Boston Harbor and the deep navigational channels around the Harbor Islands are generally composed of high backscatter, bedrock, cobble, or dense sand bars. The inner and outer harbor are generally composed of fine sand and silt. The approaches to Boston Harbor are generally composed of fine sand and silt. The approaches to Boston Harbor are generally composed of fine sand and silt. The approaches to Boston Harbor are generally composed of fine sand and silt.

Low-relief mud areas are characterized by local slopes of less than 1 degree, predominantly low backscatter intensity, and fine-grained muddy sediments, confirmed by the sampling survey. Low-relief mud areas are characterized by local slopes of less than 1 degree, predominantly low backscatter intensity, and fine-grained muddy sediments, confirmed by the sampling survey. Low-relief mud areas are characterized by local slopes of less than 1 degree, predominantly low backscatter intensity, and fine-grained muddy sediments, confirmed by the sampling survey.

Antropogenic modification features have been altered by human activity. The most widely identified man-made artifacts are dredged channels and moorage areas. The sea floor of Boston Harbor has been extensively modified by other activities, including the disposal of dredge spoils, placement of artificial reefs, construction of piers, laying of cables, and submerged reefs. Most of the features are located in the inner harbor and approaches to Boston Harbor. Antropogenic modification features have been altered by human activity. The most widely identified man-made artifacts are dredged channels and moorage areas. The sea floor of Boston Harbor has been extensively modified by other activities, including the disposal of dredge spoils, placement of artificial reefs, construction of piers, laying of cables, and submerged reefs. Most of the features are located in the inner harbor and approaches to Boston Harbor.

Acknowledgments
Funding for this program was provided by the Coastal and Marine Geology Program of the U.S. Geological Survey (USGS) and the Massachusetts Office of Coastal Zone Management (CMZ). We thank Susan Stewart-Coffey and Tony Williams of CMZ for their encouragement and support and the Civil Service Bureau and the Chief of the U.S. Geological Survey for facilitating the use of NOAA hydrographic datasets. Brian Anderson, Dave Backlund, James Derry, David Foster and Ben Jones of the USGS provided the field sampling data. Brian Anderson, James Derry and William Crocker helped in data processing and preparing GIS products. Dana Newman arranged the Open File Report in HTML. This report benefited from reviews by James Derry, Mike Butman, and Tony Wilber.

References
Ackerman, S., Butman, B., Barnhardt, W.A., Danforth, W.W., and Crocker, J.M., 2006. High-resolution geologic mapping of the inner continental shelf: Boston Harbor and Approaches. U.S. Geological Survey Open File Report OFR 2006-1008, 1:60,000.

Butman, B., Valentine, P.C., Danforth, W.W., Hayes, L., Semei, L.A., and Middleton, J.T., 2004. Shaded-relief bathymetric intensity and sea floor topographic elevation datasets for the Boston Harbor and Approaches of Boston, Massachusetts. U.S. Geological Survey Geologic Investigation Map 14734, scale 1:250,000, 2 sheets. Available online at <http://pubs.usgs.gov/ofr/2004/1008/>.

NOAA, 1996. National Oceanic and Atmospheric Administration. National Ocean Survey Special Projects Office, 1996. Sidescan Bathymetry. NCS Special Projects Website at <http://hatteras.noaa.gov/ncs/ncsproj.html>.



Map of other available seafloor mapping products. Area to the north is the Nahant's Coastline area (Barnhardt and others 2006) and shown in light gray in Massachusetts Bay (Butman and others 2006).